



Contractor Select Plus Black/Grey



Contractor's Select Plus is a flatbond polypropylene fabric that is used in many professional landscape & geotextile applications.
Contractor's Select Plus is designed to allow air, water, and nutrients to pass through the fabric.

Property	Test Method	Unit	Minimum Average
Material			Polypropylene
Weight	ASTM D 5261	OZ/SY	2.5
Grab Tensile	ASTM D 4632	LBS	MD 93
			XMD 104
Grab Elongation	ASTM D 4632	%	MD 64
			XMD 88
Trapezoid Tear	ASTM D 4533	LBS	MD 36
			XMD 47
CBR Puncture	ASTM D 6241	LBS	141
Thickness	ASTM D 5199	MILS	11
Water Permeability	ASTM D 4491	GAL/MIN/SF	17

<u>Date: 1/5/2018.</u> This data sheet supersedes all previously issued data. The above properties are typical averages.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS, SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS THE DATE COMPLIED. HOWEVER NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILTY TO SATISIFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER ANY WARRANTY AGAINST PATENT INFRINGEMENT.